

AES-5SF0036M0A

SKU: 221517



1/3" Mini Dome, Fix, clear 3,6mm, 960TVL, 12VDC, vandalism protect, flush mount

Main Features

1/3" Fix dome camera with Sony CCD	White-coloured aluminium die-cast casing
Integrated lens F2.0/3.6mm	Clear Lexan bubble, 57mm
Resolution of 960 horizontal lines	Easy indoor installation
Automatic shutter control	For in-ceiling flush mounting
Digital signal processing (DSP)	Vandal resistant
Automatic white balance (ATW)	

Specifications

General:	
Dimensions (HxWxD)	58,5x88
Illumination	no
Supply voltage	12VDC, 12VDC
Series	eneo COAXIZE
Housing	Outdoor
Color (housing)	white
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Mounting	Flush mount

AES-5SF0036M0A

Continuation of the specifications

Power consumption	1.2W
Vandal proof	yes
Operating temperature	-10°C ~ +50°C
Protection rating	IP66
Weight	200 g
DORI:	
Observe (62 px/m)	12,6 m
Recognize (125 px/m)	5,9 m
Identify (250 px/m)	2,8 m
Detect (25px/m)	32,2 m
Functions:	
Motion detector	no
Digital noise reduction (DNR)	yes
e-PTZ support	no
Camera:	
Imager	Sony Super HAD II Interline Transfer, CCD, CCD
Automatic electronic shutter (ESC)	1/50 ~ 1/120,000sec.
Backlight compensation	BLC
Low speed shutter	no
Manual electronic shutter (MES)	1/50 ~ 1/120,000sec.
Signal-to-noise ratio	50dB
Day&Night mode	Automatic
White balance	ATW
Wide Dynamic Range (WDR)	no, no
System	electronic Day&Night
Sensor size	1/3"
Day&Night switch	Electronic
Sensitivity	0,1 Lux at F1,2, 50 IRE
Camera type	Dome
Parts supplied:	
Parts supplied	manual, screw set, bag of screws
Lens:	
Lens Type	fixed focal length
Focal Length	3,6 mm
Digital Zoom	no
MOD (Mininum Object Distance)	0,1 m
Interfaces / Inputs/ Outputs:	
External connectors	12VDC input (DC plug), Composite (FBAS), connection cable approx. 25cm
Video outputs	Composite (CVBS)
Alarm inputs	no
Alarm outputs	no

AES-5SF0036M0A

Continuation of the specifications

Serial interfaces	no
Video:	
Synchronization	internal
Horizontal resolution	960 TVL
Other	
Active picture elements	976(H) x 582(V) pixels
Video standard	PAL
Low Speed Shutter	no
Digital Noise Reduction	yes
Backlight Compensation	BLC
Motion Detector	no
Objektiv Typ	fixed focal length
Horizontal Angle of View	68°
Illumination	no
Manufacturer order number	221517

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

